

Amendments to the Claims

This listing of claims replaces all prior versions and listings of claims in the application:

1. (Canceled)
2. (Previously Presented) The valve of claim 6 wherein the throttling cage is offset in the cavity away from the second fluid passage.
3. (Previously Presented) The valve of claim 6 wherein the annular volume is smallest in an area of the cavity opposite the second fluid passage.
4. (Previously Presented) The valve of claim 6 wherein at least one of the flow ports facing the second fluid passage is larger than at least one of the other flow ports.
5. (Previously Presented) The valve of claim 6 wherein a flow port facing the second fluid passage is larger than any of the other flow ports.
6. (Previously Presented) A valve comprising:
 - a valve body defining an interior cavity in communication with a first fluid passage and a second fluid passage, the volume of the cavity substantially equally distributed about a central axis;
 - a tubular throttling cage in the cavity and in communication with the first fluid passage, the tubular throttling cage positioned such that an annular volume is defined between the throttling cage and a wall of the cavity and having a plurality of flow ports arranged about a perimeter of the throttling cage, wherein fluid flows between the first fluid passage and the second fluid passage through the throttling cage, a longitudinal axis of the throttling cage is positioned offset from the central axis of the cavity, and the flow ports are angled towards the second fluid passage; and

a plug closely received in the throttling cage and moveable about the longitudinal axis to selectively cover the flow ports thereby restricting flow between the first fluid passage and the second fluid passage.

7. (Previously Presented) The valve of claim 6 wherein walls of the flow ports pass substantially straight through the throttling cage.

8. (Previously Presented) The valve of claim 6 wherein the throttling cage has a triangular flow splitter.

9. (Original) The valve of claim 8 wherein the triangular flow splitter is in the portion of the throttling cage opposite the second fluid passage.

10. (Previously Presented) The valve of claim 6 wherein the throttling cage is substantially sealed to the valve body.

11. (Canceled)

12. (Previously Presented) The fluid flow control device of claim 14 wherein at least one of the lateral ports is larger than the other lateral ports.

13. (Previously Presented) The fluid flow control device of claim 14 wherein a lateral port facing the second fluid passage is larger than at least one of the other lateral ports.

14. (Currently Amended) A fluid flow control device, comprising:
a flow body having an internal chamber;
a first fluid passage intersecting the chamber;
a second fluid passage intersecting the chamber;
a tubular member residing in the internal chamber, the tubular member being in communication with the first fluid passage and having a plurality of lateral ports, wherein the substantially all of the lateral ports are angled direct fluid flow towards the second fluid passage;
and

a plug adapted for movement in an interior of the tubular member to selectively cover a portion of the ports;

wherein an annular volume between the tubular member and the flow body is smallest opposite the second fluid passage.

15. (Previously Presented) The fluid flow control device of claim 14 wherein walls of the lateral ports pass substantially straight through the tubular member.

16. (Previously Presented) The fluid flow control device of claim 14 wherein two adjacent lateral ports form a triangular flow splitter in the tubular member.

17. (Original) The fluid flow control device of claim 16 wherein a lateral port opposite the triangular flow splitter is larger than at least one of the other lateral ports.

18. (Currently Amended) A throttling cage for a globe valve, comprising:
a tubular body having a plurality of laterally oriented flow ports, walls of the flow ports being substantially straight through the tubular body, wherein ~~one~~ substantially all of the ports ~~directs direct flow in towards~~ a first direction, ~~and at least one other port is angled to direct flow towards the first direction.~~

19. (Original) The throttling cage of claim 18 wherein one of the flow ports is larger than the other flow ports.

20. (Original) The throttling cage of claim 18 wherein at least one of the flow ports is larger than at least one of the other flow ports.

21. (Original) The throttling cage of claim 18 wherein two adjacent flow ports form a triangular flow splitter.

22. (Currently Amended) A valve comprising:

a valve body defining an interior cavity in communication with a first fluid passage and a second fluid passage;

a tubular throttling cage in the cavity having an open end in communication with the first fluid passage and a plurality of flow ports arranged about a perimeter of the throttling cage, walls of the flow ports being substantially straight through the throttling cage, wherein one substantially all of the flow ports directs direct flow in towards a first direction ~~and at least one of the other ports is angled to direct flow towards the first direction~~, and wherein fluid flows between the first fluid passage and the second fluid passage through the throttling cage; and

a plug closely received in the throttling cage and moveable in the throttling cage to selectively cover the flow ports thereby restricting flow between the first fluid passage and the second fluid passage.

23. (Original) The valve of claim 22 wherein at least one of the flow ports is larger than at least one of the other flow ports.

24. (Original) The valve of claim 22 wherein an annular volume between the throttling cage and a wall of the cavity is smallest in an area of the cavity opposite the second fluid passage.

25. (Canceled)

26. (Previously Presented) The valve of claim 27 wherein a lateral flow port facing the outlet is larger than at least one of the other lateral flow ports.

27. (Currently Amended) A valve, comprising:
a flow body having an internal chamber;
an inlet intersecting the chamber;
an outlet intersecting the chamber;
a tubular member residing in the internal chamber, the tubular member in communication with the inlet and having a plurality of lateral ports in communication with the chamber, wherein ~~at least two~~ substantially all of the lateral ports ~~are angled~~ direct flow towards the outlet; and
a plug movable in an interior of the tubular member to selectively cover a portion of the ports;
wherein an annular volume between the tubular member and the flow body is smallest opposite the outlet.

28. (Previously Presented) The valve of claim 27 further comprising a triangular flow splitter in the tubular member opposite the outlet.